

Gree GA Series PTAC

Performance, Physical Data and Unit Specifications

Call your Gree Sales Representative for additional technical data.







COOLING AND ELECTRIC HEAT

MODEL NUMBER	Cooling Capacity (BTUH)	EER	Reverse Cycle Heat (BTUH)	Electric Heat Capacity	COP	Voltage 1-ph 60 hz	Cooling Amperes (Amps)	Cooling Power (Watts)	Approx. Ship Weight (Lbs)
PTAC-GAE07AB-D	7600/7700	12.2/12	N/A	Determined by your power cord selection. See chart below.	N/A	208/230	3.0/2.8	620/640	121
PTAC-GAE09AB-D	8800/9000	11.4/11.3	N/A		N/A		3.9/3.7	770/800	128
PTAC-GAE12AB-D	11800/12000	10.5/10.7	N/A		N/A		5.3/5.1	1120/1120	137
PTAC-GAE15AB-D	15000/14600	9.8/9.7	N/A		N/A		7.5/6.7	1510/1530	143
PTAC-GAE07AB-P	7700	12	N/A		N/A	265	2.4	640	121
PTAC-GAE09AB-P	9000	11.3	N/A		N/A		3.7	800	128
PTAC-GAE12AB-P	12000	10.7	N/A		N/A		4.8	1120	137
PTAC-GAE15AB-P	15000	9.8	N/A		N/A		5.9	1530	143

HEAT PUMPS

MODEL NUMBER	Cooling Capacity (BTUH)	EER	Reverse Cycle Heat (BTUH)	Electric Heat Capacity	COP	Voltage 1-ph 60 hz	Cooling Amperes (Amps)	Cooling Power (Watts)	Approx. Ship Weight (Lbs)
PTAC-GAA07AB-D	7600/7700	12.2/12	6100/6300	Determined by your power cord selection. See chart below.	3.4/3.4	208/230	3.0/2.8	620/640	121
PTAC-GAA09AB-D	8800/9000	11.4/11.3	7900/8100		3.3/3.3		3.9/3.7	770/800	128
PTAC-GAA12AB-D	11800/12000	10.5/10.7	10500/10700		3.1/3.1		5.3/5.1	1120/1120	137
PTAC-GAA15AB-D	15000	9.8	13800		2.9		6.7	1530	143
PTAC-GAA07AB-P	7700	12	6300		3.4	265	2.4	640	121
PTAC-GAA09AB-P	9000	11.3	8100		3.3		3.7	800	128
PTAC-GAA12AB-P	12000	10.7	10700		3.1		4.8	1120	137
PTAC-GAA15AB-P	15000	9.8	13800		2.9		5.9	1530	143

POWER CORD SELECTION GUIDE

Model Number	Voltage	Receptacle Type	Heating (BTUH)	Heater (Kw)	Input Power (WH)	Current (Amps)	Branch Circuit Full Amps
PWRCORD-230V-15A	208/230V	 15 amp/250V	5,630/6,950	1.635/2.0	1,643/2,047	8.0/8.9	15
PWRCORD-230V-20A		 20 amp/250V	8,650/10,390	2.453/3.0	2,496/3,036	12.2/13.2	20
PWRCORD-230V-30A		 30 amp/250V	13,780/16,990	4.089/5.0	4,118/5,037	20.5/21.5	30
PWRCORD-265V-15A	265V	 15 amp/277V	6,820	2.0	2,120	8.9	15
PWRCORD-265V-20A		 20 amp/277V	10,470	3.0	3,127	13.2	20
PWRCORD-265V-30A		 30 amp/277V	17,110	5.0	5,035	21.5	30

Power Cord Selection

Gree GA Series PTACs are not individually equipped with a power cord, so one must be ordered separately based on the voltage and amperage of your electrical circuit. If the unit is to be plugged into a receptacle, then a line cord connection kit needs to be selected. If it will be permanently connected, a hardware connection kit must be used.

NOTE: In compliance with UL and the National Electrical Code, 265V units installed with a power cord require the use of a 265V electrical subbase.



© Gree 2010

GA-PTAC-006-2010-1

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations. Before purchasing this appliance, please read the important energy cost and efficiency information available from your dealer.



Always look for these symbols, the air conditioning and heat pump industry seals of certified performance, efficiency and capacity.